

## PRODUKT Information: FOILS / GAZES

ITEM	MATERIAL	MAKE-UP	COUNT	USE	APPLICATION
SOLVY	70% PVAL / 15% VG/ 7% PSAC / 8% additives	50 cm x 25 m	approx. 25 g / m <sup>2</sup>	put on top and underneath	soluble in warm water
SOLVY		33 cm x 100 m			
SOLVY		100 cm x 100 m			
SOLVY FILM 20	70% PVAL / 15% VG/ 7% PSAC / 8% additives	50 cm x 25 m	approx. 27 g / m <sup>2</sup>	Embroidery background	soluble in warm water
SOLVY FILM 20		100 cm x 100 m			
SOLVY FILM 80	75 % PVAL / 25 % additives	50 cm x 25 m	approx. 100 gr/m <sup>2</sup>	Embroidery background	soluble in warm water
SOLVY FILM 80		100 cm x 100 m			
THERMOGAZE	100% CV	40 cm x 25 m	98 g / m <sup>2</sup>	Embroidery background	soluble in heat
THERMOGAZE		80 cm x 100 m			
THERMOGAZE		160 cm x 100 m			
THERMOFILM	100% PE	50 cm x 25 m	27 g / m <sup>2</sup>	put underneath	soluble in heat
THERMOFILM		100 cm x 300 m			
THERMOFIX	100% PA	50 cm x 25 m	50 g / m <sup>2</sup>	Adhesive fibers	perm. Iron on / press
THERMOFIX		50 cm x 100 m			
BSN-H	100 % PA silicon paper	37,5 cm x 25 m	60 g / m <sup>2</sup>	Ironing foil - press	Household washing up to 40°C
BSN-H		37,5 cm x 100 m			
BSN-H		75 cm x 100 m			
BSN-I	100 % PA silicon paper	37,5 cm x 25 m	80 g / m <sup>2</sup>	Ironing foil - press	Industrial washing up to 60°C
BSN-I		37,5 cm x 100 m			
BSN-I		75 cm x 100 m			
STICK PROTECT	100% PES coating: 100% PA	50 cm x 25 m	53 g / m <sup>2</sup>	Protective fabric / fixing interlining	iron on
STICK PROTECT		150 cm x 180 m			
GUDY STIC	82 % CV / 18 % PES, coating: 100 % PAK,	40 cm x 25 m	30 g / m <sup>2</sup>	Appliqués	glue, laminate
GUDY STIC		122 cm x 25 m			
TS	100% PU	25 cm x 10 m	228 g / m <sup>2</sup>	Adhesive film - heat press	sealing
TS		50 cm x 10 m			
HEAT STIC	100 % PES coating: 100 % PAK	50 cm x 25 m	162 g / m <sup>2</sup>	Appliqués	to press on
HEAT STIC		50 cm x 300 m			